

# DIGITAL POWERSPIN™ LX PRO

Model: C85608



- POWERSPIN™ LX PRO CENTRIFUGE
- VARIABLE SPEED 1000-4000 RPM
- 8 PLACE FIXED ANGEL ROTOR
- 99 MIN DIGITAL TIMER
- CAPACITY 8X10 ML TUBES
- VETSCAN IMAGYST™ COMPATIBLE



The C85608 PowerSpin™ LX Centrifuge offers digital variable speed control from 300 to 4,000 RPM, providing flexibility for different sample types. With an 8-place rotor and a 99-minute digital timer, it can accommodate up to 8 x 15ml tubes, making it ideal for a wide range of laboratory applications. Specifically, the C85608 model, equipped with a 8-place rotor, is ideal for processing fecal samples, making it perfectly compatible with the VETSCAN IMAGYST™ system for parasite detection and other veterinary diagnostic tests. This centrifuge meets top safety and electromagnetic compatibility standards for reliable operation in laboratory environments. It complies with UL 61010-1:2012, CAN/CSA-C22.2 NO.61010-1-12, and IEC 61010-2-020:2016 for safety. It also adheres to FCC Part 15 Subpart B: 2017 and IEC60950-1:2006 for electromagnetic compatibility, ensuring safe, interference-free use in labs globally.



## ADDITIONAL INFORMATION

<b>TOP SELECTION</b>	Yes
<b>SHIPPING WEIGHT</b>	22 lb
<b>SHIPPING SIZE</b>	Shipping Length 20 Shipping Height 16 Shipping Width 18
<b>ACCESSORIES</b>	<p><b>Accessories</b></p> <p>C800-75 Tachometer, Laser Digital with Reflective Tape, Batteries, In A Storage Case</p> <p>C8000-02 Regular Tube Shield, White, pack of 2</p> <p>C8000-03-8 5 ml Adapter for short tubes, pack of 8</p>
<b>SPECIFICATION</b>	<p><b>Number of Tubes</b> 8</p> <p><b>Tube Capacity</b> 8-15 ml</p> <p><b>Blood</b> Yes</p> <p><b>Specimens Fecal</b> Yes</p> <p><b>Urine</b> Yes</p> <p><b>Microhematocrit</b> With Adapters</p> <p><b>Speed</b> Variable</p> <p><b>Rotor</b> Fixed Angle</p> <p><b>Maximum RPM</b> 4000</p> <p><b>Maximum RCF(g)</b> 1860</p>
<b>SIZE AND WEIGHT</b>	<p><b>Shipping Size</b> 20 in x 16 in x 18 in</p> <p><b>Weight</b> 21 lbs</p> <p><b>Shipping Weight</b> 22 lbs</p>
<b>WARRANTY</b>	1 years

